

Declaration of Performance:

TT20 & TT21-CPR-2022



Product:

Product type/application: Room heater burning solid fuel without hot water supply.

Type:

TT20Bazic, TT20Bazic R, TT20, TT20S, TT20R, TT20RS, TT21R, TT21RS, TT21RS Black, TT21RS-GREY TT21RL, TT21RLS, TT21RH, TT21RHS, TT21SA, TT21RS-WH, TT21RS-SA, TT21RHT, TT21RS-CG

Fuel:

Wood (Birch)

Productions No:

Please see nameplate on the back of the stove.

Manufacturer:

TermaTech A/S
Gunnar Clausens Vej 36
8260 Viby J
Denmark

E-mail: info@termatech.com
Web: www.termatech.com
Tel.: +45 8742 0035

Certification and requirements:

AVCP system: System 3
European standard: CE/DS/DIN/EN 13240:2001 + A2:2004/AC2007

United Kingdom: CPR 2011 (Retained EU law EUR 305/2011) as amended.
Standard: BS Standard, BS EN 13240: 2001+A2:2004
KIWA Ltd. Approved Body No. 0558. Report No. 61678

Certification: Technologic Institute, notified body no. 1235, has performed determination of the product type and declared performance on the basis of type testing and issued test report no. 300-ELAB-2618-EN + KIWA Ltd. Approved Body No. 0558. Report No. 61678

Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	AI	CE/DS/DIN/EN 13240:2001+ A2:2004/AC2007 Ecodesign 2015/1185
Distance to combustible materials	Rear: min. 150 / 100mm Sides: min. 350 mm To the corner 45° min. 125mm/125mm Other safety distances – please see User and mounting manual	
Emission of combustion products	CO = 0,06 % NOx = 89 mg/Nm ³ OGC = 44 mgC/Nm ³ PM = 17 mg/Nm ³	
Electrical safety	NPD	
Maximum operating pressure	NPD	
Risk of burning fuel falling out	Passed	
Surface temperature	Passed	
Clean ability	Passed	
Mechanical strength	Passed	
Emission of hazardous materials	Passed	
Flue gas temperature	261° Celsius	
Output	5,0 KW	
Energy efficiency	81 %	

The undersigned is responsible for the manufacturing and conformity with the declared performance.

Viby 09.08.2022

Søren Toft

