

# Declaration of Performance

TT30-CPR-2016-Version 3



## Product:

Product type/application: Room heater burning solid fuel without hot water supply  
Type: **TT30:** S01-730, **TT30G:** S01-732/738, **TT30S:** S01-734,  
**TT30GS:** S01-736  
Fuel: Wood  
Productions no. Please see nameplate on the back of the Stove

## Manufacturer:

TermaTech A/S  
Gunnar Clausens Vej 36  
8260 Viby J  
Denmark  
E-mail: [info@termatech.com](mailto:info@termatech.com)  
Web: [www.termatech.com](http://www.termatech.com)  
Tel.: +45 8742 0035

## Certification and requirements:

AVCP system: System 3  
European standard: EN 13240:2001/AC:2006 + EN13240:2001/A2:2004/AC:2007  
Certification: Rhein-Ruhr Feuerstätten Prüfstelle GmbH, notified body no. 1625, has performed determination of the product type and declared performance on the basis of type testing and issued test report no.RRF-40 15 4171 + RRF - 40 19 5364-1

## Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	AI	The DS/EN 13240:2001 / A2:2004 / AC:2007
Distance to combustible materials	<b>TT30 + TT30S:</b> Rear: min. 150 / 100 mm Sides: min. 250 / 350 mm To corner 45°: min. 250 mm <b>TT30G + TT30GS:</b> Rear: min. 150 /100 mm Sides: min. 490 mm To corner 45°: min. 490 mm Other safety distances – please see User and mounting manual	
Emission of combustion products	CO = 0,07 % NOx = 107 mg/m <sup>3</sup> OGC = 75 mgC/Nm <sup>3</sup> PM = 17 mg/m <sup>3</sup>	
Electrical safety	NPD	
Maximum operating pressure	NPD	
Risk of burning fuel falling out	Passed	
Surface temperature	Passed	
Clean ability	Passed	
Mechanical strength	Passed	
Emission of hazardous materials	Passed	
Flue gas temperature	273° Celsius	
Output	5 KW	
Energy efficiency	81 %	

undersigned is responsible for the manufacturing and conformity with the declared performance.

